

# ManuTel<sup>®</sup> Manual Telescopic Forks

Efficient and safe



Fork and extension in one product - this is ManuTel<sup>®</sup> by VETTER. Easy! Efficient! Flexible!

- ▶ Efficient application: truck loading / unloading from one side or loading of 2 or 3 pallets at once
- ▶ High safety: Always the right blade length!
- ▶ Solid construction, suitable for all-terrain application
- ▶ Significant time and cost savings compared to common fork extensions
- ▶ Easy application without tools or hydraulics
- ▶ Quick release pin-locking device for easy length adjustment



## MANUTEL<sup>®</sup> G2 STANDARD EDITION

- ▶ Ideal for truck loading and unloading from one side
- ▶ Wear-resistant straight manganese steel plate on the lower side of the fork shoe
- ▶ Wide product range: Standard capacity up to 12,600 lbs @ 24" load center, custom-made capacities on demand



## MANUTEL<sup>®</sup> SLIMLINE EDITION

- ▶ Extra-thin blade - thickness only 1.5"
- ▶ Ideal for loads and pallets with small fork pockets
- ▶ Capacity up to 3,600 lbs

The illustrations only represent the basic principles and do not constitute a contractual entitlement.



**ROI CALCULATION**



Common fork extension: approx. 10 minutes mounting time (search, carry, fit, lock, ... remove, carry, transport, etc.)  
 NEW! ManuTel® **< 1 minute required (unlock, extend, lock - READY!) = 9 minutes time savings**

Based on an hourly rate of \$57.00 USD (lift truck / driver) and 240 working days, time savings **2,160 minutes**

**= COST SAVINGS \$ 2,052.00 USD**

per year - with only one change of blade length per day!



**EFFICIENT**

Truck loading and unloading from one side or transport of 2 or 3 pallets at once



**SAFE**

Always the right fork length! No risk of accident by protruding or short fork blades.



**SOLID**

ManuTel® G2 for all-terrain use, long operating lifetime and efficient use.



**SIMPLE**

ManuTel® Telescopic-Forks are ready to use within seconds, without tools or additional hydraulics!



**1000-FOLD APPROVED**

World-wide in all types of environments.

The illustrations only represent the basic principles and do not constitute a contractual entitlement.

## MANUTEL<sup>®</sup> product range

### MANUTEL<sup>®</sup> G2

Type ManuTel <sup>®</sup> Art. No.	Capacity @ LC lbs/inch	Fork length		Basic fork section inch	Sleeve section inch	Weight / piece lbs	„C of G“		ITA class
		(retracted) LO (inch)	(extended) L1 (inch)				(retracted) (inch)	(extended)	
MTUS37/32/48/A	3,700 / 24"	32"	48"	1.4" x 4.8"	2.0" x 5.3"	121	10.4	14.1	2
MTUS37/42/60/A	3,700 / 24"	42"	60"	1.4" x 4.8"	2.0" x 5.3"	149	15.0	19.4	2
MTUS37/48/72/A	3,700 / 24"	48"	72"	1.4" x 4.8"	2.0" x 5.3"	165	17.8	23.9	2
MTUS37/60/96/A	3,700 / 24"	60"	96"	1.4" x 4.8"	2.0" x 5.3"	196	23.4	33.1	2
MTUS55/32/48/A	5,500 / 24"	32"	48"	1.5" x 5.0"	2.3" x 5.5"	153	9.6	12.7	2
MTUS55/42/60/A	5,500 / 24"	42"	60"	1.5" x 5.0"	2.3" x 5.5"	184	14.1	17.9	2
MTUS55/48/72/A	5,500 / 24"	48"	72"	1.5" x 5.0"	2.3" x 5.5"	202	16.7	22.1	2
MTUS55/60/96/A	5,500 / 24"	60"	96"	1.5" x 5.0"	2.3" x 5.5"	239	22.2	30.7	2
MTUS79/42/60/A	7,900 / 24"	42"	60"	1.8" x 6.0"	2.4" x 6.5"	240	14.2	17.6	3
MTUS79/48/72/A	7,900 / 24"	48"	72"	1.8" x 6.0"	2.4" x 6.5"	264	16.8	21.6	3
MTUS79/60/96/A	7,900 / 24"	60"	96"	1.8" x 6.0"	2.4" x 6.5"	311	22.3	29.9	3
MTUS100/42/60/A	10,000 / 24"	42"	60"	2.0" x 6.0"	2.5" x 6.5"	262	14.3	17.5	3
MTUS100/48/72/A	10,000 / 24"	48"	72"	2.0" x 6.0"	2.5" x 6.5"	288	16.9	21.4	3
MTUS100/60/96/A	10,000 / 24"	60"	96"	2.0" x 6.0"	2.5" x 6.5"	339	22.4	29,5	3
MTUS126/48/72/A	12,600 / 24"	48"	72"	2.0" x 7.0"	2.5" x 7.7"	375	15.5	19.4	4
MTUS126/60/96/A	12,600 / 24"	60"	96"	2.0" x 7.0"	2.5" x 7.7"	437	20.7	27.1	4

**Intermediate lockings on demand!**

### MANUTEL<sup>®</sup> SLIMLINE

Type ManuTel <sup>®</sup> Art. No.	Capacity @ LC lbs/inch	Fork length		Basic fork section inch	Sleeve section inch	Weight / piece lbs	„C of G“		ITA class
		(retracted) LO (inch)	(extended) L1 (inch)				(retracted) (inch)	(extended)	
MTSKUS36/32/48/A	3,600 / 24"	32"	48"	1.4" x 5.5"	1.5" x 5.6"	114	9.5	12.0	2
MTSKUS36/42/60/A	3,600 / 24"	42"	60"	1.4" x 5.5"	1.5" x 5.6"	138	14.0	19.9	2
MTSKUS36/48/72/A	3,600 / 24"	48"	72"	1.4" x 5.5"	1.5" x 5.6"	151	16.7	20.8	2

**Intermediate lockings on demand!**

Further sizes on request!  
Delivery including operating manual!

The illustrations only represent the basic principles and do not constitute a contractual entitlement.