

Recommended standard-section in relation between blade length and rated truck capacity

Suspension class ISO	Rated lift truck capacity up to ... kg	Load center (mm)	Recommended section for blade length			
			800 mm - 1,900 mm		2,000 mm - 2,500 mm	
			ISO-A	ISO-B	ISO-A	ISO-B
2	1,800	500	100 x 35 80 x 40	100 x 35 80 x 40	100 x 40	100 x 40 100 x 45
	2,000	500	80 x 40 100 x 40	80 x 40 100 x 40	100 x 45 120 x 40	100 x 50 120 x 40
	2,500	500	100 x 40 100 x 45 120 x 40	100 x 40 100 x 45 120 x 40	100 x 45 125 x 45	100 x 50 120 x 40
3	3,000	500	100 x 45 100 x 50 125 x 45	100 x 50 120 x 50	125 x 45 120 x 50	125 x 45 120 x 50
	3,500	500	100 x 50 125 x 45	100 x 50 120 x 50	125 x 45 120 x 50	120 x 50 150 x 50
	4,000	500	125 x 45 120 x 50	120 x 50 140 x 50	120 x 50 140 x 50	140 x 50 150 x 50
	4,500	500	120 x 50 140 x 50 150 x 50	120 x 50 140 x 50 150 x 50	140 x 50 150 x 50	140 x 50 150 x 50
	5,000	500	140 x 50 150 x 50	130 x 60 150 x 50	130 x 60 150 x 50	130 x 60 150 x 50
4	5,000	600	130 x 60	130 x 60	130 x 60 150 x 60	130 x 60 150 x 60
	6,000	600	130 x 60 150 x 60	150 x 60	150 x 60 150 x 70	150 x 60 150 x 70
	7,000	600	150 x 60 150 x 70	150 x 65 150 x 70	150 x 65 150 x 70	150 x 70
	8,000	600	150 x 65 150 x 70	150 x 70	150 x 70	150 x 70
	9,000	600	150 x 70	150 x 70	150 x 75	150 x 75
	10,000	600	150 x 75	150 x 75	180 x 70 200 x 70	180 x 70 200 x 70
5	on request					

ATTENTION:

Different load centres have a significant influence on the selection of the cross-section. Ask for details!

The illustrations only represent the basic principles and do not constitute a contractual entitlement.
 Technical information will not be updated automatically.